

TECUMSEH



R.B.	Šifra robe	Naziv proizvoda	Primedba
HERMETIČKI (KLIPNI) KOMPRESORI			
AE2 kompresori-monofazni (usis/potis-na varenje)			
HBP (-25, 15 oC), R 134a, To/Tc=+5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"-/+ " režim rada
1	TC-AE4430Y	AE 4425Y (6,69 cm3) Q=530 W	usis/potis=6,35x4,76 mm (FR 7,5GX)
2	TC-AE4430Y	AE 4430Y (8,02 cm3) Q=684 W	usis/potis=6,35x4,76 mm (FR 10GX)
3	TC-AE4440Y	AE 4440Y (10,33 cm3) Q=830 W	usis/potis=7,9x6,35 mm (SC 12GX)
4	TC-AE4450Y	AE 4450Y (13,24 cm3) Q=1.153 W	usis/potis=9,5x6,35 mm (SC 15GX)
5	TC-AE4456Y	AE 4456Y (14,51 cm3) Q=1.255 W	usis/potis=9,5x6,35 mm (SC 18GX)
CAJ kompresori-monofazni (usis/potis-na varenje)			
LBP, R 404A, To/Tc=-25/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=57K, Trg=+32oC)			na varenje (bez rotalock priključaka)
LBP, R 404A, To/Tc=-25/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=57K, Trg=+32oC)			"-" režim rada
6	TC-CAJ 2446Z	CAJ 2446Z (26,2 cm3) Q=812 W	usis/potis=12x8 mm (GS 26CLX) 2258730106
7	TC-CAJ 2464Z	CAJ 2464Z (34,5 cm3) Q=1.072 W	usis/potis=16x10 mm (GS 34CLX) 2258831106
MHBP, R 404A, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			
MHBP, R 404A, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"+" režim rada
8	TC-CAJ 9510Z	CAJ 9510Z (18,3 cm3) Q=1.640 W	usis/potis=16x8 mm (GS 21MLX) 2256330106
9	TC-CAJ 9513Z	CAJ 9513Z* (24,2 cm3) Q=2.000 W	usis/potis=16x8 mm 2256431106
10	TC-CAJ 4517Z	CAJ 4517Z* (25,95 cm3) Q=2.344 W	usis/potis=16x10 mm (GS 26MLX) 2256831106
11	TC-CAJ 4519Z	CAJ 4519Z* (34,45 cm3) Q=2.822 W	usis/potis=16x10 mm (GS 34MLX) 2256930106
HBP, R 22, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			
HBP, R 22, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"+" režim rada
12	TC-CAJ 9510T	CAJ 9510T (18,3 cm3) Q=2.238 W	usis/potis=16x8 mm 2254530106
13	TC-CAJ 9513T	CAJ 9513T (24,2 cm3) Q=2.892 W	usis/potis=16x8 mm 2255230106
14	TC-CAJ 4517E	CAJ 4517E (25,95 cm3) Q=3.227 W	usis/potis=16x10 mm 2254730106
15	TC-CAJ 4517T	CAJ 4517T (25,95 cm3) Q=3.227 W	usis/potis=16x10 mm AJ4TL1JF606A06
16	TC-CAJ 4519T	CAJ 4519T (32,7 cm3) Q=4223 W	usis/potis=16x10 mm 2254090106
HBP, R 134a, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			
HBP, R 134a, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"+" režim rada
17	TC-CAJ 4492Y	CAJ 4492Y (25,95 cm3) Q=1.235 W	usis/potis=12x8 mm (GS 26MFX) 2257330102
18	TC-CAJ 4511Y	CAJ 4511Y (32,7 cm3) Q=1.681 W	usis/potis=16x8 mm (GS 34MFX) 2257530106

THF/TAG kompresori-trofazni (usis/potis-na Rotalock)			Rotalock navojni priključci (usis/potis)
HBP, R 22, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"+" režim rada
19	TC-TFH 4522F	TFH 4522F* (39,95 cm3) Q=2.898 W (sa grejačem ulja) bez rotalock ventila	usis/potis=5/8"x1/2" mm (MT 22-4VM) 2565830124 Rotalock ventili(DL):V09 (usis)/V06 (potis)
20	TC-TFH 4531F	TFH 4531F* (56,65 cm3) Q=4.472 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x1/2" (MT 32-4VM) 2566230124 Rotalock ventili(DL):V05 (usis)/V06 (potis)
21	TC-TFH 4540F	TFH 4540F* (74,25 cm3) Q=5.687 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x1/2" (MT 40-4VM) 2566430124 Rotalock ventili(DL):V05 (usis)/V06 (potis)
22	TC-TAG 4553T	TAG 4553T (100,7 cm3) Q=7.011 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x5/8" (MT 57-4VM) 2831030105 Rotalock ventili(DL):V05 (usis)/V09 (potis)
23	TC-TAG 4568T	TAG 4568T* (124,4 cm3) Q=9.137 W (sa grejačem ulja, sa TC rotalock ventilima)	usis/potis=1 1/8"x5/8" (MT 64-4VM/MT 72-4VM) Rot. vent.(TC):1 1/4(1 1/8") (usis)/1 1/4(5/8") (potis)
24	TC-TAG 4573T	TAG 4573T* (134,8 cm3) Q=9.778 W (sa grejačem ulja, sa TC rotalock ventilima)	usis/potis= 1 1/8"x5/8" (MT 80-4VM) Rot. vent.(TC):1 1/4(1 1/8") (usis)/1 1/4(5/8") (potis)

THF/TAG kompresori-trofazni (usis/potis-na Rotalock)			Rotalock navojni priključci (usis/potis)
HBP, R 404A, To/Tc=-5/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=37K, Trg=+32oC)			"+" režim rada
25	TC-TFH 4522Z	TFH 4522Z* (39,95 cm3) Q=5.687 W (sa grejačem ulja) bez rotalock ventila	usis/potis=5/8"x1/2" (MTZ 22-4VM) 2565030124 Rotalock ventili(DL):V09 (usis)/V06 (potis)
26	TC-TFH 4531Z	TFH 4531Z* (56,65 cm3) Q=5.687 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x1/2" (MTZ 32-4VM) 2565430124 Rotalock ventili(DL):V05 (usis)/V06 (potis)
27	TC-TFH 4540Z	TFH 4540Z* (74,25 cm3) Q=5.423 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x1/2" (MTZ 40-4VM) 2565630124 Rotalock ventili(DL):V05 (usis)/V06 (potis)
28	TC-TAG 4568Z	TAG 4568Z* (124,4 cm3) Q=5.687 W (sa grejačem ulja, sa TC rotalock ventilima)	usis/potis=7/8"x1/2" (MTZ 64-4VM/MTZ 72-4VM) Rot. vent.(TC):1 1/4(1 1/8") (usis)/1 1/4(5/8") (potis)
29	TC-TAG 4573Z	TAG 4573Z* (134,8 cm3) Q=9.514 W (sa grejačem ulja, sa TC rotalock ventilima)	usis/potis=1 1/8"x5/8" (MTZ 80-4VM) 2836230102 Rot. vent.(TC):1 1/4(1 1/8") (usis)/1 1/4(5/8") (potis)

THF/TAG kompresori-trofazni (usis/potis-na Rotalock)			Rotalock navojni priključci (usis/potis)
LBP, R 404A, To/Tc=-25/+55 oC (Cecomaf, ΔTsc=0K, ΔTsh=57K, Trg=+32oC)			"-" režim rada
30	TC-TFH 2480Z	TFH 2480Z* (53,2 cm3) Q=1.490 W (sa grejačem ulja) bez rotalock ventila	usis/potis=5/8"x1/2" (NTZ048A4LR1) 2567030124 Rotalock ventili(DL):V09 (usis)/V06 (potis)
31	TC-TFH 2511Z	TFH 2511Z* (74,2 cm3) Q=1.969 W (sa grejačem ulja) bez rotalock ventila	usis/potis=5/8"x1/2" (NTZ068A4LR1) 2567230124 Rotalock ventili(DL):V09 (usis)/V06 (potis)
32	TC-TAG 2516Z	TAG 2516Z* (112,5 cm3) Q=2.883 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x5/8" (NTZ108A4LR1) 2835030105 Rotalock ventili (DL): V05 (usis)/V09 (potis)
33	TC-TAG 2522Z	TAG 2522Z* (134,8 cm3) Q=3.673 W (sa grejačem ulja) bez rotalock ventila	usis/potis=7/8"x1/2" (NTZ136A4LR1) 2835230105 Rotalock ventili: 1 1/4-1 1/8" (usis)/1 1/4"-5/8" (potis)

Rotalock ventili - DENA LINE

34	DL-V05	Rot. ventil V09 (1 1/4"-12 UNF/ODS 5/8")	TFH 4522F/TFH 4522Z
35	DL-V06	Rot. ventil V06 (1"-14UNS/ODS 1/2")	
36	DL-V05	Rot. ventil V05 (1 1/4"-12 UNF/ODS 7/8")	TFH 4531F/TFH 4531Z/TFH 4540F
37	DL-V06	Rot. ventil V06 (1"-14UNS/ODS 1/2")	TFH 4540Z

38	DL-V05	Rot. ventil V05 (1 1/4"-12 UNF/ODS 7/8")	TAG 4553T, TAG 2516Z
39	DL-V09	Rot. ventil V09 (1 1/4"-12 UNF/ODS 5/8")	

KOMPRESORSKO-KONDENZATORSKI AGREGATI		nizak nivo buke-za supermarkete	
CAJN kompresorsko-kondenzatorski agregati			
MHBP, R 404A, To/Tc=-5/+55 oC (EN13215, ΔTsc=3K, ΔTsh=15K, Trg=+20oC)		"+" režim rada	
40	TC-CAJN 4517Z	CAJN 4517ZHR (Q=2.640 W)	usis/tečni vod=5/8"x3/8" (Kp,Kd, Res.,El. kutija)
41	TC-CAJN 4519Z	CAJN 4519ZHR (Q=3.335 W)	usis/tečni vod=5/8"x3/8" (Kp,Kd,Res.,El. kutija)